

Thermoplastic Hose...

Food • Chemical • Oil • Beverage • Automotive • Water • Air • Fuels



Thermoplastic Hose...

Food • Chemical • Oil • Beverage • Automotive • Water • Air • Fuels

FlexTECH stock a comprehensive range of thermoplastic hose and tubes made from many compound variations to ensure that PVC hoses are available to satisfy many different applications.


Thermoplastic hose can be supplied in coil lengths, specific bespoke lengths or assembled with hose couplings utilising either a simple clamping method or our specially designed hygienically swaged interlocking coupling system.



SpringFlex Series T1900 food grade non toxic wire reinforced smooth bore PVC hose suitable for the suction and delivery of foodstuffs, granules, and dilute chemicals.
Sizes: from 13mm to 152mm
Pressures: up to 12 Bar
Temperatures: -15°C to + 65°C
Braided version available for pressures up to 30 Bar



ExtraFlex Air Hose Series T1211 light weight superflexible reinforced PVC air hose for general workshop use and hand held air tools.
Sizes: from 6mm to 19mm
Pressures: up to 18 Bar
Temperatures: -15°C to + 65°C
Standard colours are Blue, Black & Red




Braided PVC Series T1200 food grade low toxic reinforced PVC pressure hose to ISO 5774. Ideal for pressure transfer of air, liquids, gases and dilute chemicals.
Sizes: from 5mm to 52mm
Pressures: up to 25 Bar
Temperatures: -15°C to + 65°C




Tanker Hose Series T1760SE is a medium weight suction hose made from super elastic compound. This is a very flexible, robust hose with the added benefit of an external scuff strip. Perfect for the transfer of water, slurry and sewage to and from gully tankers
Sizes: from 25mm to 254mm
Pressures: up to 7.5 Bar
Temperatures: -15°C to + 65°C



Extraflex Series T1300 general purpose flexible water hose designed for agricultural and horticultural use.
Sizes: from 13mm, 19mm & 25mm
Pressures: 10 Bar working
Temperatures: -15°C to + 65°C
Alternatively ask for details of genuine **Tricoflex...**



PVC Tubing Series T1000 food grade low toxic un-reinforced PVC tubing. Ideal for low pressure liquids, dilute chemicals, air and gases applications.
Sizes: from 3mm to 52mm
Pressures: limited
Temperatures: -15°C to + 65°C




GreenTint Series T1800 lightweight PVC suction and delivery general purpose hose with rigid helical spiral. Used in the agricultural, marine and pumping industries.
Sizes: from 13mm to 102mm
Pressures: up to 10 Bar
Temperatures: -15°C to + 65°C
Also available in clear food grade series T1690.



Green MDS Series T1750 medium duty PVC suction hose ideal for higher pressure or suction applications which demand a longer lasting hose.
Sizes: from 25mm to 254mm
Pressures: up to 10 Bar
Temperatures: -15°C to + 65°C
Series T1850 Heavy Duty grey for working pressures up to 13 Bar.




GPA Air Hose Series T1230 general purpose air hose made from a nitrile/PVC alloy mix which offers excellent flexibility & kink resistance making this an ideal alternative to traditional rubber hose.
Sizes: from 5mm to 25mm
Pressures: 20 Bar Working
Temperatures: -25°C to + 65°C



Blue Oil Series T1600 medium duty oil transfer hose is formulated from nitrile PVC mix and designed for the transportation of low aromatic fuel oils such as diesel, kerosene, white spirit and mineral based hydraulic oils.
Sizes: from 25mm to 254mm
Pressures: up to 10 Bar
Temperatures: -15°C to + 65°C



Fire Reel Hose Series T1310 red first aid fire reel hose. This hose is tough, highly flexible, kink resistant and manufactured to EN694 standards.
Sizes: 19mm and 25mm
Pressures: 12 Bar
Temperatures: -15°C to + 65°C



Blue Oil Series T1600 medium duty oil transfer hose is formulated from nitrile PVC mix and designed for the transportation of low aromatic fuel oils such as diesel, kerosene, white spirit and mineral based hydraulic oils.
Sizes: from 25mm to 254mm
Pressures: up to 10 Bar
Temperatures: -15°C to + 65°C



Diesel Drop Hose Series T1320 is designed specifically for the transfer of fuel oils with a low aromatic content such as diesel, kerosene, white spirit and mineral based hydraulic oils.
Sizes: 19mm and 25mm
Pressures: 12 Bar
Temperatures: -15°C to + 65°C



Nylon Tubing Series T1110 semi-rigid nylon 11 and 12 Tubings conforms to BS 5409 Pt 1:1976. Available in 12 colours and manufactured in both metric & imperial sizes for pneumatic applications.
Sizes: from 3 to 28mm & 1/8" to 1"
Pressures: up to 2,500 PSI size dependant
Temperatures: -15°C to + 80°C

Nylon Air-Coils Series T1120 semi-rigid nylon 11 and 12 Air-Coils conforms to BS 5409 Pt 1:1976. The coils are available in 12 colours and manufactured in both metric and imperial sizes.
Sizes: from 3mm to 25mm
Pressures: up to 30 Bar
Temperatures: -15°C to + 80°C

Layflat Hose Series T1500 industrial grade light discharge layflat hose for use with water and slurry. Available in blue light weight and yellow medium weight.
Sizes: from 25mm to 200mm
Pressures: up to 9 Bar (type dependant)
Temperatures: -25°C to + 65°C